



NOTES:

1. 2" MINIMUM DIAMETER RESTRICTOR PIPE ALLOWED. USE ONLY COMMERCIALY AVAILABLE SCHEDULE 40 PIPE DIAMETER SIZES.
2. WHEN RESTRICTOR PIPE IS 6" DIAMETER OR LESS, CASING PIPE SHALL BE MINIMUM 12" DIAMETER RCP.
3. WHEN RESTRICTOR PIPE IS 6" DIAMETER OR GREATER, CASING PIPE SHALL BE THE CLOSEST RCP PIPE DIAMETER SIZE EQUAL TO TWICE (DOUBLE) THE RESTRICTOR DIAMETER.
4. WHEN RESTRICTOR STRUCTURE IS LOCATED OFF OF PAVEMENT, A PROPER SECTIONED, TEN FOOT (10') WIDE PAVED PATH SHALL BE INSTALLED FROM THE CLOSEST PAVED HARD SURFACE TO THE RESTRICTOR STRUCTURE.



REVISIONS

DATE: 4/2018	BY: DGoewey

RESTRICTOR STRUCTURE TYPE A

SCALE: NONE	CHECKED: TD
DATE: 4/2018	DRAWN: DGoewey

DRAWING NUMBER EXHIBIT IV-C-4A
--