



NOTES:

LOCATE SERVICE CONNECTION AT THE MAIN. DEPLOY AND MAINTAIN ALL NECESSARY TRAFFIC CONTROL. EXCAVATE AND EXPOSE CONNECTION AT THE MAIN.

- ① IF A TEE OR WYE WAS USED TO CONNECT THE OLD SERVICE AND SAID TEE OR WYE IS IN SOUND CONDITION, SNAP OFF THE SERVICE PIPE ONE (1) FOOT FROM THE MAIN, INSTALL A MECHANICAL TWIST PLUG SIX (6) INCHES INSIDE THE SERVICE PIPE, THEN FILL THE REMAINING PIPE WITH MORTAR. PLUG THE END OF THE ABANDON SERVICE WITH NON-SHRINK GROUT.
- ② IF THE EXISTING CONNECTION WAS A BREAK-IN CONNECTION, AND THE BREAK-IN CONNECTION IS IN SOUND CONDITION, SNAP OFF THE SERVICE PIPE ONE (1) FOOT FROM THE MAIN, INSTALL A MECHANICAL TWIST PLUG SIX (6) INCHES INSIDE THE SERVICE PIPE, THEN FILL THE REMAINING PIPE WITH MORTAR. PLUG THE END OF THE ABANDON SERVICE WITH NON-SHRINK GROUT.

AFTER ALL WORK IS INSPECTED, BACKFILL AND RESTORE THE AREA PER APPROPRIATE CITY STANDARD SPECIFICATIONS.



ENGINEERING

REVISIONS

DATE:	BY:
04-18	DGoewey

SAN SEWER ABAN - Type A

SCALE:	CHECKED:
NOT TO SCALE	JB
DATE:	DRAWN:
4/17	DG

DRAWING NUMBER:
EXHIBIT III-G-4