



NOTES:

LOCATE SERVICE CONNECTION AT THE MAIN. DEPLOY AND MAINTAIN ALL NECESSARY TRAFFIC CONTROL. EXCAVATE AND EXPOSE CONNECTION AT THE MAIN.

- ① IF A TEE OR WYE WAS USED TO CONNECT THE OLD SERVICE AND SAID TEE OR WYE IS IN SOUND CONDITION, SNAP OFF THE SERVICE PIPE ONE (1) FOOT FROM THE MAIN, INSTALL A MECHANICAL TWIST PLUG SIX (6) INCHES INSIDE THE SERVICE PIPE, THEN FILL THE REMAINING PIPE WITH MORTAR. PLUG THE END OF THE ABANDONED SERVICE WITH NON-SHRINK GROUT.
- ② IF THE EXISTING CONNECTION WAS A BREAK-IN CONNECTION, AND THE BREAK-IN CONNECTION IS IN SOUND CONDITION, SNAP OFF THE SERVICE PIPE ONE (1) FOOT FROM THE MAIN, INSTALL A MECHANICAL TWIST PLUG SIX (6) INCHES INSIDE THE SERVICE PIPE, THEN FILL THE REMAINING PIPE WITH MORTAR. PLUG THE END OF THE ABANDONED SERVICE WITH NON-SHRINK GROUT.
- ③ IF THE TEE, WYE, OR BREAK IN CONNECTION IS NOT IN SOUND CONDITION, THE TEE, WYE, OR BREAK IN CONNECTION SHALL BE REMOVED AND A CONNECTION TO THE EXISTING SANITARY SEWER SHALL BE MADE USING A NON-SHEER MISSION COUPLING.

AFTER ALL WORK IS INSPECTED, BACKFILL AND RESTORE THE AREA PER APPROPRIATE CITY STANDARD SPECIFICATIONS.



REVISIONS

DATE:	BY:
04-18	DGoewey
02-22	CArmin

SAN SEWER ABAN (TYPICAL) - Type A

SCALE:	CHECKED:	DRAWING NUMBER:
NOT TO SCALE	JB	
DATE:	DRAWN:	EXHIBIT III-G-4
4/17	DG	